



## TDM2400P

### Scalable and Effective SME Solution

The Wildcard TDM2400P is a full-length 32-bit 33MHz PCI 2.2-compliant card that supports quad FXS station and quad FXO office interfaces (for a total of 24 maximum channels on a single PCI slot) for connecting analog telephones and lines through a PC. The TDM2400P can be used to connect standard analog telephone lines to a PC and Asterisk.

Using Digium's TDM hardware, Asterisk PBX software, and standard PCs, users can create an SME or SOHO telephony environment that includes all the sophisticated features of a high-end PBX/Voicemail platform.

Using an industry-standard bursting, bus-mastering PCI interface chip, and Digium's patent-pending *VoiceBus* technology, the TDM2400P eliminates the requirement for separate channel bank and T1 interface cards, at an industry leading price. The quad-FXO and quad-FXS modules are interchangeable, allowing the creation of any combination of interfaces. The optional hardware echo cancellation module provides 256 taps of echo cancellation for superior echo cancellation on both FXO and FXS interfaces. Scaling of this solution is accomplished by adding additional TDM2400P cards.

For more information on the TDM2400P, please visit the *Products* section of [dtasia.com.au](http://dtasia.com.au).



## Target Applications

---

Channel Bank Replacement /Alternative  
Small Office Home Office (SOHO) applications  
Small and Medium Enterprise (SME) applications  
Gateway Termination to analog telephones and lines

## Services and Features

---

Caller ID and Call Waiting Caller ID  
ADSI Telephones  
PCI Full-length Slot  
RJ-21 Connector

## Environment Conditions

---

Operation Range: 0° to 50°C,  
32° to 122° F  
Storage Range: -20° to 65°C,  
4° to 149° F  
Humidity: 10-90% non-condensing

## Standard Configurations

---

Six slots for 4-port FXS or FXO  
modules  
Hardware Echo cancellation  
module available

## Modules

---

S400M: Quad FXS Module  
X400M: Quad FXO Module  
VPM100M  
G.168 Echo Can. Module, 32ms Tail  
/ 256 Taps, 1 per TDM2400P

## Hardware and Software Requirements

---

1.4 GHz Pentium 4 or better with  
64MB RAM  
Available Full-length PCI Slot

For more information please contact:

## Digital Techniques (Asia) Limited

Unit 306, 3/F, B2B Centre  
36 Connaught Road West  
Sheung Wan  
Hong Kong

Tel: +852 2517 0933  
Email: [sales@dtasia.net](mailto:sales@dtasia.net)  
Web: [www.dtasia.net](http://www.dtasia.net)